implantswiss

UCLA ABUTMENT

(Cast Abutment)



» Used for cement retained restorations
» Can be used when have aesthetic or space limitations
» After customization, prosthetic must be produced by casting

implantswiss

BONE LEVEL MINI UCLA ABUTMENT



GH	
1mm	S-BMUA10
2mm	S-BMUA20
3mm	S-BMUA30
4mm	S-BMUA40

BONE LEVEL MINI UCLA ABUTMENT NON-HEX



GH	
1mm	S-BMUAN10
2mm	S-BMUAN20
3mm	S-BMUAN30
4mm	S-BMUAN40

BONE LEVEL UCLA ABUTMENT



GH	
1mm	S-BUA10
2mm	S-BUA20
3mm	S-BUA30
4mm	S-BUA40

BONE LEVEL UCLA ABUTMENT NON-HEX



GH	
1mm	S-BUAN10
2mm	S-BUAN20
3mm	S-BUAN30
4mm	S-BUAN40

Abutment material:	CoCr Alloy Melting range: 1307-1417°C
Abutment plastic cylinder material:	Polyoxymethylene (POM)
Abutment screw:	Ti Grade 5 ELI
Packing unit:	UCLA abutment + abutment screw (S-BMSAS (mini), S-BAS (regular))
Required Screwdriver:	1.2mm Hex